

WATER QUALITY MONITORING
AND SAMPLING

2EA

WATER QUALITY INSPECTIONS

24MONTHS

CONSTRUCT AND REMOVE
BALED STRAW

6000LF

MAINTENANCE OF
BALED STRAW

3000LF

TEMPORARY PIPE
SLOPE DRAIN

5000LF

TO BE USED AS DIRECTED BY ENGINEER

PLAIN CONCRETE
DITCH PAVING, 4 IN.

13000SQ YD

TO BE USED AS DIRECTED BY ENGINEER

MULCH

AS REQUIRED3000 TN

GRASSING			AGRICULTURAL LIME	FERTILIZER MIXED GRADE	FERTILIZER NITROGEN CONTENT	LIQUID LIME
ITEM	UNIT	ACRE	TON	TON	LB	GL
PERMANENT GRASSING		145	118	24	5879	294
ADDITIONAL GRASSING	LBS					
TOTAL			118	24	5879	294

TEMPORARY GRASSING

117ACRES

* NOTE: = TO BE USED AT LOCATIONS
SHOWN ON THE PLANS AND / OR AS
DIRECTED BY ENGINEER

USE ON
CONSTRUCTION

MULKEY

ENGINEERS & CONSULTANTS

1255 CANTON STREET, SUITE G
ROSWELL, GEORGIA 30075
(678) 461-3511

REVISION DATES		
3-26-07		

STATE OF GEORGIA DEPARTMENT OF TRANSPORTATION	
OFFICE:	
SUMMARY QUANTITIES EROSION CONTROL	
DRAWING No. 6-19	